





## **SW900X**

## **Professional Pass-through Warewasher**

## **SW900X Specifications**

DIMENSIONS (WXDXH)	633 x 755 x 1565 mm
HOOD CONSTRUCTION	Insulated double-skinned
HOOD OPENING	465 mm
HOOD LIFT SYSTEM	ProGlide (3 kg)
HOOD LIFT HANDLE	all-around
WASH CHAMBER	TotalClean - Pipe Free
RACK STAND CONSTRUCTION	S/S wire hinged
TANK VOLUME	22 litres
TANK CONSTRUCTION	deep drawn
TANK HEATING ELEMENT	2,5kW
WASH PUMP TYPE	Double flow
WASH PUMP POWER	700 W
RINSE SYSTEM	SmartRinse
RINSE BOOSTER PUMP	Fitted
SELF DIAGNOSTIC SYSTEM	Fitted
BOILER HEATING ELEMENT	6,0 KW
FRESH WATER CONSUMPTION	2,3 lt/rack
DRAIN SYSTEM	SmartDrain (partial drain)
DRAIN PUMP	Fitted
DOSING SYSTEM	ProDose electr. Controlled
DETERGENT & RINSE AID PUMP	Fitted
TOTAL ELECTRIC LOAD AT 415V (3PH+N+E)	6,7 kW
WASH CYCLES	60, 90, 120 sec
SPECIAL CYCLES	3
SELF CLEANING CYCLE	YES
WATERMARK APPROVAL	WMKT25317
HACCP APPROVAL	PE-388-GE-09

Dimensions may change without notice in accordance with product development and design

**Proudly Distributed By** 

## eswood.com.au

211–217 Woodpark Road SMITHFIELD NSW 2164
T: 1800 013 123
E: sales@middleby.com.au



